

LT1040

MINI EXCAVATOR



PRODUCT INFORMATION

Certification:

ISO CE EPA EURO5

Bucket capacity	0.12m³	Travel speed	2.7/4.5km/h
Operating weight	4000kg	Max. digging height	4920mm
Volume of fuel tank	41L	Max. dumping height	3490mm
Engine brand	YAMMAR 3TNV88F	Max. digging depth	3165mm
Rated power	18.2kw/2200rpm	Max. digging radius	5260mm
Intake mode	Self-priming	Arm digging force	24kN
Fuel system mode	Direct injection	Bucket digging force	30kN
Emission standard	EPA Tier4F & EC STAGE 3A	Traction	38.5kN
Drive mode	Hydraulic	Swing speed	9.5r/min
Main pump flow	99Mpa		
Rated flow	100Mpa		
Track width	300mm		
Max climbing degree	35°		



PRODUCT DETAIL



The LT1040 model bagger adopts Yammar diesel engine, meets Euro V and EPA4 emission standards, meets environmental protection requirements, Low noise, Kubota engine parts are universal.



A

Cab

Operation buttons and switches are within easy reach, improving work efficiency



D

Open Cab

Operators can observe changes in objects within the working range more clearly and clearly



B

Bucket Teeth

Bucket teeth are made from high-tensile and wear-resistant steel plates



E

Steel Tracks

Durable, stable, adaptable to various terrains and working environments



C

Operating Lever

Simple, flexible and easy to operate.